

SITARA-6S/6D



Salient Features



- ♦ **Pairing**
Any transmitter & receiver can be paired on-site (for easy spare management)
- ♦ **Adjustable Range**
Operating Range Adjustment (from 10m to 100m)
- ♦ **Adjustable Start Range**
Only START functionality can be range adjustable
- ♦ **Password**
Transmitter password protection
- ♦ **Frequency Change**
Operating channel can be changed on site
- ♦ **Idle Time**
Configurable Idle Time out in Transmitter

Additional Features

Emergency STOP	2 NC contacts for EMS (EN-954-1 Safety Standard)
Indication	LED Indication for Battery LOW, Transmission and Error status
Address Code	Unique Address Code to avoid interference
Antenna	Internal Antenna in transmitter & receiver
Relay Assignment	Configurable Relay assignment available
Auxillary Functions	Selector Switch / Toggle Switch/ Push Buttons /Rotary Switch

Transmitter

Operating Frequency	433-434 Mhz
Channel Spacing	25 KHz
Modulation	FM (4GFSK/2GFSK)
RF Power Output	10 mW
Power Consumption	18 mA (Unidirectional)
Standby Power Consumption	1 mA
Battery Capacity and Type	2 nos, AA size Alkaline, 3.0V
Operating Temperature	-20°C to +70°C
Weight	200 gms (without battery)
Dimensions (mm)	69 (H) X 34 (W) X 169 (B)
Operating Range	100 meters
Protection Rating	IP 65 IS/IEC 600529:2001

TRANSMITTER	RECEIVER
	
SITARA - 6S	SITARA-6D
6 Pushbutton Single speed	6 Pushbutton Double speed

Technical Specification

Number of commands in Transmitter unit SITARA-6S	6 + Start/Stop + Alarm
Number of commands in Transmitter unit SITARA-6D	12 + Start/Stop + Alarm
CRC	32 Bit
Response Time	<50 ms
Active Emergency Response Time	<50 ms
Passive Emergency Response Time	1900 ms

Receiver

Operating Frequency	433-434 Mhz
Channel Spacing	25 KHz
RF Sensitivity	-117dBm at 0.6kbaud
Number of Relays SITARA-6S	6 + 2 (Start/Alarm)
Number of Relays SITARA-6D	9 + 2 (Start/Alarm)
Relays	Resistive load: 5A at 250VAC
Power Requirements	48VAC - 230VAC
Fastening	By means of Nuts & Bolts
Operating Temperature	-20°C to +70°C
Weight	Approx 0.5 Kg
Dimensions (mm)	165 (H) x 150 (B) x 72 (W)
Operating Range	100 meters
Protection Rating	IP 65